Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or	trade mark: Nordlux
Supplier's address:	Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model	idontifior	2080101458
woder	iaenuner:	ZUMUTUT45M

Type	٥f	liaht	SOLI	rco.
IVDE	UI	IIKIIL	SUU	ıce.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	_		

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
<u> </u>	mption in on- 00 h), rounded st integer	3	Energy efficiency class	G	
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200	
On-mode pow pressed in W	ver (P _{on}), ex-	3,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	97	Spectral power dis-	See image	
sions without	Width	35	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	35	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime-					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	21		
		Chromaticity coordinates (x and y)	0,502 0,415		
Parameters for LED and OLED li	Parameters for LED and OLED light sources:				
R9 colour rendering index value	9	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,98	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-': not applicable; (b)'-': not applicable;

