Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or | trade mark: | Nordlux |
|--------------------|-------------|---------|
|--------------------|-------------|---------|

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 2019041035

| _ | • | | | |
|------|-----|--------|----------------|----|
| Typa | Λt | liaht | sourc | Δ. |
| IVDE | OI. | IIGIIL | 3 Uui C | c. |

| Type of light source: | | | | |
|-------------------------------|------------|---------------------------------|-------|--|
| Lighting technology used: | LED | Non-directional or directional: | NDLS | |
| Light source cap-type | LED Module | | | |
| (or other electric interface) | | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No | |
| Colour-tuneable light source: | No | Envelope: | - | |
| High luminance light source: | No | | | |
| Anti-glare shield: | No | Dimmable: | No | |
| Product parameters | | | | |
| Parameter | Value | Parameter | Value | |
| | | | • | |

| Product parameters | | | | |
|---|---|-------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| | | General product p | parameters: | |
| Energy consur mode (kWh/10 up to the neare | 00 h), rounded | 8 | Energy efficiency class | F |
| dicating if it refe a sphere (360º) | s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º) | 800 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 7,5 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| (P _{net}) for CLS, 6 | andby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |
| Outer dimen- | Height | 160 | Spectral power dis- | See image |
| sions without | Width | 60 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 115 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | |
|---|--|--|----------------|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | |
| | | Chromaticity coordinates (x and y) | 0,463 0,422 | |
| Parameters for LED and OLED I | ight sources: | | | |
| R9 colour rendering index value | 9 0 | Survival factor | 0,90 | |
| the lumen maintenance factor | 0,96 | | | |
| Parameters for LED and OLED r | Parameters for LED and OLED mains light sources: | | | |
| displacement factor (cos φ1) | 0,00 | Colour consistency in McAdam ellipses | 6 | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | : | If yes then replace- ment claim (W) | - | |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 0,9 | |

(a)'-': not applicable; (b)'-': not applicable;

