Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Nordl	ux
---	----

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 2213550103

Type of light source	e:	:	
----------------------	----	---	--

Lighting technology used:	LED	Non-directional or	NDLS	
		directional:		
Light source cap-type	Ledmodule			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light	No	
		source (CLS):		
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				
Parameter	Value	Parameter	Value	

		i rodact parar		I
Parameter		Value	Parameter	Value
General product parameters:				
<u> </u>	mption in on- 00 h), rounded st integer	4	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	350 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P _{on}), ex-	4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	-
(P _{net}) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	38	Spectral power dis-	See image
sions without	Width	82	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	82	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,458			
		nates (x and y)	0,410			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,95					
Parameters for LED and OLED m	Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,1			

(a)'-': not applicable; (b)'-': not applicable;

