Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Nordlux

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 2112203003

Type of light source:

Lighting technology used:	LED	Non-directional or	DLS
		directional:	
Light source cap-type	LED Module		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light	No
		source (CLS):	
		source (CES):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
	1		

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neares	00 h), rounded	4	Energy efficiency class	F		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	320 in Nar- row cone (90°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	2 700		
On-mode pow pressed in W	ver (P _{on}), ex-	3,2	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
(P _{net}) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen- sions without separate con-	Height Width Depth	120 1 180 35	Spectral power dis- tribution in the range 250 nm to 800	See image in last page		
trol gear, light- ing control			nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,463			
		nates (x and y)	0,420			
Parameters for directional light sources:						
Peak luminous intensity (cd)	5 563	Beam angle in de- grees, or the range of beam angles that can be set	41			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	1,00			
the lumen maintenance factor	0,95					
(a)	1	1				

(a)'-' : not applicable;

(b)'-' : not applicable;

