Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Nordlux	(
---	---

Supplier's address: Nordlux A/S, Østre Havnegade 34, 9000 Aalborg, DK

Model identifier: 2019051035

Type of light source	Type	of light	source:
----------------------	------	----------	---------

LED	Non-directional or directional:	NDLS
LED Module		
MLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	LED Module MLS No No	directional: LED Module MLS Connected light source (CLS): No Envelope: No

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
_ ·	nption in on- 00 h), rounded st integer	11	Energy efficiency class	F	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 051 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pow pressed in W	ver (P _{on}), ex-	10,6	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	220	Spectral power dis-	See image	
sions without	Width	60	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	160	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,437 0,398	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9	

(a)'-': not applicable; (b)'-': not applicable;

